

24 Spectra High Performance Piezoelectric Jetting Assembly prints at **True 300 dpi**



Safety guards control switches

Mesh Adaptors



Safety guards with UV Protection

Intuitive user interface



Choice of Rips for different operating systems:
Onyx | Wasatch SoftRip | Caldera



High / Low vacuum system



Steel Frame Construction

Rewind (Take Up) Unit is built in

Safety Shut Off



GANDINNOVATIONS
where innovation meets perfection

Jeti 5024 UV JETSPEED RTR

Jeti 5024 Jetspeed UV Roll to Roll

The **Jeti 5024 UV Jetspeed** is now available in a 4 Color configuration, featuring 24 Spectra print heads. The UV lamps instantly dries the UV-curable Premium inks, these specially formulated inks yield a wider color gamut and exhibit excellent flexibility and superior adhesion on a variety of materials fabric, canvas, vinyl, plastic film, paper and polyester including 100% PE eco-friendly opening many new markets. Capable of printing fast high quality images at speeds of 1,177 sqft/hr (109 sqm/hr) in 3-pass Billboard mode at 300 dpi, which is perfect for Outdoor application. Designed for 24/7 productivity with a single operator intervention The **Jeti 5024 UV Jetspeed** maximizing speeds and cost effectiveness for end-users, is the best productive digital solution for outdoor applications in speed and quality for billboards and building wraps. The **Jeti 5024 UV Jetspeed** gives the perfect print every time, with brighter images and solid colors using dedicated environmentally friendly UV-curable Premium inks, these specially formulated inks yield a wider color gamut and exhibit excellent flexibility and superior adhesion on a variety of materials including 100% PE eco-friendly. This complete printing solution provides an economic advantage for our customers. At the forefront of the technological enhancements is the software upgrade, which can detect if any individual nozzle may be misfiring. This safe-proof technology is the first of its kind in the grand-format area. The **Jeti 5024 UV Jetspeed** also includes an automatic head capping feature (auto caps in 15 minutes if machine sets) and automated air vacuum system that eliminates manual head wiping.

Technical Specifications

Technology	Spectra High Performance Piezoelectric Jetting Assembly, quantity 24.	Weight	8500 lbs / 3855 kgs uncrated. Add 3000 lbs / 1360 kg for crating.
Print Resolution	Prints quality at True 300 dpi - 4 color.	Printer Dimensions	72" h x 51" w x 308" l (182cm x 130cm x 782cm) Crated dims: 90" h x 72" w x 326" l.
Media Dimensions	Roll max size: 5.1 meter / 16'8" wide. Max diameter is .3281m (12") on a 7.62cm (3") inside core.	Power Consumption	25 KVA (35A).
Media Types	Reinforced vinyl, pressure sensitive vinyl, canvas, fabrics, mesh, paper and 100 % PE Material.	Electrical Requirements	400Y / 230V, 3 Phase 50/60 Hz.
Printing Speeds	IMPROVED SPEEDS on all resolutions, call for latest speeds on True 600 dpi and 300 dpi.		

Click, call or come down to see our full range of Grand Format Digital Printers.



Accessories (Included)	Rewind (Take Up) Unit (<i>built in</i>), Roll Lifter, Safety Guards (<i>built in</i>).
Supported Platforms	Microsoft Windows, Apple Machintosh, Linux.
Processors	P4 (3.4 GHz).
Interpreter	Custom - Gandinnovations Software Development.
Network	10/100/1000 Mbit/sec Ethernet.
Protocols	Ethertalk and TCP/IP.
Monitor	420mm (17 inch) LCD Flat panel Display.
Operator Console	Rotatable shelf with keyboard, mouse and monitor.
Input Formats	Adobe Postscript Level 3, Pdf, Jpeg, Tiff, Eps, RGB.
Rips	Includes your choice from:- Wasatch SoftRip, Onyx or Caldera.
Compressed Air	80 PSI minimum - 100 PSI maximum with a 10 gallon (40 liter tank) 5 cfm peak.
Inks	Shelf life is 1 year for UV Inks. UV Inks will last 1-2 years depending on location.
Special Inks	UV white or UV clear varnish can be added as spot colors.
Environment	Enclosed dust free room with ambient temperatures ranging from 20°C - 23°C (68°F - 73°F). Relative Humidity 40% to 55% to operate at optimum level (<i>Environment is critical for the printer</i>).
Warranty	1 year warranty on all parts including print heads, labor valid with the use of Gandinnovations original inks and parts. Extended warranty available on printer.
Services	Online Technical Support, 8:00am - 8:00pm (<i>eastern standard</i>) Monday - Friday, Fully qualified service engineers available onsite (<i>within 24 hrs</i>). T: 1 866 500 JETi (North America).

Gandinnovations - North America
Hary Gandy

C: 1 210 241 8511
 F: 905 502 9360
 E: northamerica@gandigroup.com

Marketing - Worldwide

Tom Reilly
 5975 Falbourne Street,
 Mississauga, Ontario L5R 3V8
 Canada

T: 905 361 6982
 F: 905 502 9360
 E: marketing@gandigroup.com

Gandinnovations U.S.A
Media & Inks

Cory Brock
 941 Isom Road
 San Antonio, TX 78216 U.S.A.
 T: 1 866 500 JETi
 F: (210) 344 9569
 E: consumables@gandigroup.com

Gandinnovations - Europe
Patrick Pittoors

Ann Robaye
 Generaal de Wittelaan 7a
 2800 Mechelen
 Belgium
 T: +32 (0) 15 460 204
 F: +32 (0) 15 460 205
 E: europe@gandigroup.com

Middle East & Africa

Abdallah Ghalayini
 Regional Managing Director ME&A
 Gandinnovations FZCO
 Dubai Airport Free Zone
 East Wing 1 - Office 110
 Dubai - United Arab Emirates
 T: +971 4 299 69 69
 F: +971 4 299 41 19
 USA Mobile : +1 413 885 5600
 UAE Mobile : +971 50 798 6590

Gandinnovations - South East Asia
Ann Ng

Regional Manager
 Gandinnovation Asia Pacific
 Unit F, 7/F, Sunview Industrial Building,
 No 3 On Yip Street
 Hong Kong
 Singapore : +65 9658 1348
 Hong Kong : +852 9333 2033
 E: southeastasia@gandigroup.com

Gandinnovations - India
Chandan Mishra

T: +91 98203 32555
Manesh Shetty
 T: +91 98206 44007
Pradeep Satyanarayana
 T: +91 98802 84246
 F: +91 22289 78242
 E: india@gandigroup.com

Gandinnovations - South America
Cristian Gonzales

T: (404) 451 5856
 E: latinamerica@gandigroup.com

Gandinnovations - Mexico

Carlos Guzman
 Gandinnovations S.A. De C.V.
 Calzada San Simon # 27,
 Col San Simon Tolnahuac,
 Delegacion Cuauhtemoc,
 Mexico DF CP 06920
 T: +52 55 3946 0096
 F: +52 55 3946 0091
 E: mexico@gandigroup.com

click, call or come in.